



ASPHALT BICYCLE/PEDESTRIAN PATH TYPICAL DETAIL

NOTES:

1. BICYCLE/PEDESTRIAN PATHS SHALL BE EIGHT FEET WIDE UNLESS NOTED OTHERWISE.
2. WHERE PATHS CROSS DRIVEWAYS, THE MINIMUM SURFACE, BASE, & SUBGRADE REQUIREMENTS SHALL BE THE SAME AS REQUIRED FOR A LOCAL STREET OR THE DESIGN SPECIFICATIONS OF THE DRIVEWAY.
3. CROSS SLOPE SHALL BE TO ROADWAY AT MAXIMUM 3/16" PER FOOT (1.5%).
4. ALL ROOTS, MUCK, AND OTHER UNSUITABLE MATERIALS SHALL BE REMOVED TO A DEPTH OF 12" BELOW THE BASE ROCK.
5. ASPHALT DENSITY SHALL BE 94% OF MAXIMUM DESIGN DENSITY FOR ASPHALT MIX.



TOWN OF JUPITER
ENGINEERING DIVISION

210 MILITARY TRAIL
JUPITER, FLORIDA 33458
(561) 746-5134

Asphalt Pathway

DETAIL AND REQUIREMENTS

DETAIL NUMBER

120

Revised 20140527