


**NOTES:**

1. SPEED TABLE HEIGHT DIMENSIONS SHOWN ARE RELATIVE TO EXISTING PAVEMENT.
2. ALL CONCRETE TABLE DIMENSIONS ARE SYMMETRICAL ABOUT CENTERLINE OF TABLE.
3. CONCRETE TO BE BRICK RED COLOR THROUGHOUT, UNLESS SPECIFIED OTHERWISE.
4. SAWCUT CLEAN, STRAIGHT EDGE AT FOOTER/ASPHALT INTERFACE.
5. CONTRACTOR TO PREPARE A TEMPLATE FOR TOWN TO CONFIRM HUMP PROFILE.
6. 6"x6" W2.0xW2.0 WELDED WIRE MESH FURNISHED IN FLAT SHEETS PLACED 2" FROM TOP. ALL REINFORCING STEEL SHALL BE SUPPORTED DURING CONCRETE POUR.
7. CONCRETE TO BE 4000 PSI STANDARD MIX WITH FIBER MESH.
8. SPEED TABLE CROSS-SLOPE TO MATCH EXISTING ROADWAY CROSS-SLOPE.
9. DIRECTIONAL TRIANGLES SHALL BE PAINTED SOLID WHITE.

**SINUSOIDAL SPEED TABLE PROFILE**



**TOWN OF JUPITER**  
ENGINEERING DIVISION

210 MILITARY TRAIL  
JUPITER, FLORIDA 33458  
(561) 741-2372

**CONCRETE SPEED TABLE**

TRAFFIC CALMING DETAILS

DETAIL NUMBER

**302b**

Revised 20100820